

COMPATIBLE SYSTEMS



Recess mounted
11 mm thick



Wall mounted
24 mm thick



Video intercom
version



7" display



5-inch display



Version for the
hearing impaired



Speaker audio

Do you want a design product full of technology? Choose XTS.

This is the new range of video entry panel systems, available with 7 and 5-inch monitors - fully touch screen. The minimal design and quality of the materials exalt its elegance, whether you choose the white or black version. The high-resolution glass screen with Optical Bonding technology ensures perfect viewing in all lighting conditions. Having WiFi, both in the X1 and IP versions, makes it the choice for managing the video intercom system and opening the front door from a smartphone.

PLUS

Full-duplex speaker audio

Capacitive touch screen

Display with Optical Bonding anti-glare technology

Auxiliary/porter calls functions

Intercom calls

"Panic" key for emergency calls to the porter

Adjust/exclude ringtone (with alert LED when excluded)

Self-inserting video from entry panels

Video answering service and video recording

Local or POE power supply

AVAILABLE VERSIONS





Recess mounted



Wall mounted

DIMENSIONS (MM)





PLUS

- Half-duplex speaker audio
- 7" TFT display Full touch-screen with Optical Bonding anti-glare technology for enhanced readability in brightly lit settings
- On-board WiFi for remotely controlling calls over smartphones and tablets running the specific App
- Local power supply 14 -18 VDC
- Up to 4 mobile device for managing the system from any remote location
- Configurable quick controls: main entrance door-opener, auxiliary command
- List of AUX commands for activating auxiliary functions
- "Panic" function for emergency calls to the porter (if present on the system)
- Audio video settings: ringtone volume, display brightness, interface backgrounds
- Different melodies for entry panels and landings
- Exclude ringtone key (the alert LED lights up when silenced)
- Self-inserting video of entry panels with cyclic selection
- Intercom calls to other receivers and smartphones and tablets
- Contacts list and favorites list
- Video answering service, stores up to 100, 10-second audio and video messages.
- Audio and video recording during conversations
- Live feeds of the connected IP video cameras
- Business function: for automatic door opening during business hours
- Block display function for cleaning
- Standard SIP protocol, codec video H.264, codec audio G711
- On-board web server for configuring and managing via the browser

XTS 7 WH WIFI 840CH-0030

TECHNICAL CHARACTERISTICS

MODELS	XTS 7 WH WIFI
Dimensions (mm)	185 x 129 x 24
Local power supply (V)	14 ÷ 18 DC
Local absorption (mA)	520
Consumption in stand-by mode (mA)	360
Operating temperature (°C)	0 ÷ +40
Protection rating (IP)	30
Video standard	PAL/NTSC
Frequency (MHz)	2.412 - 2.472
Wireless Standard	IEEE 802.11b/g/n
Color	White

CODE DESCRIPTION

**XTS 7 WH WIFI
840CH-0030**

Full-touch speaker video intercom for X1 system, 7" TFT touch screen display, Wi-Fi and Graphical User Interface - white.

Wall monitor with 7" TFT touch screen display with Moth-Eye technology, integrated Wi-Fi for the remote operation of calls on smartphone with dedicated app. User interface for management of the functions of video entry phone, intercom calls, video recording. It uses the SIP protocol and G711 audio codec and H.264 video codec. 14-18 VDC local power supply. Integrated web service for configuration and firmware updates. A bracket is included for wall installation on 503 box (horizontal or vertical) and on round box Ø 60 mm. Suitable for built-in installation with dedicated box. Compatible with X1 and XIP systems.

