



## PLUS

- Full-duplex speaker audio
- 5" TFT display Full touch-screen with Optical Bonding anti-glare technology for enhanced readability in brightly lit settings
- RJ45 port for directly connecting to the Ethernet
- Local or PoE (Powered over Ethernet) power supply
- Customizable user interface with UI Creator software
- Configurable quick controls (default main entrance door-opener)
- List of AUX commands for activating auxiliary functions
- "Panic" function for emergency calls to the porter (if present on the system)
- Audio video settings: ringtone volume, display brightness, interface backgrounds
- Different melodies for entry panels and landings
- Exclude ringtone key (the alert LED lights up when silenced)
- Self-inserting video of entry panels with cyclic selection
- Unlimited calls to other receivers and smartphones and tablets
- Contacts list and favorites list
- Video answering service, stores up to 100, 10-second audio and video messages.
- Audio and video recording during conversations
- Send and receive text messages to and from the porter or other monitor extensions
- Live feeds of the connected IP video cameras
- Business function: for automatic door opening during business hours
- Block display function for cleaning
- Standard SIP protocol, codec video H.264, codec audio G711
- On-board web server for configuring and managing via the browser

## XTS 5IP WH 840CH-0090

### TECHNICAL CHARACTERISTICS

| MODELS                            | XTS 5IP WH      |
|-----------------------------------|-----------------|
| Dimensions (mm)                   | 138 X 98 X 24   |
| Local power supply (V)            | 14 ÷ 18 DC      |
| PoE power supply                  | IEEE 802.3af-PD |
| Consumption in stand-by mode (mA) | 270             |
| Max. absorption (mA)              | 330             |
| Operating temperature (°C)        | 0 ÷ +40         |
| Protection rating (IP)            | 30              |
| Video standard                    | H.264           |
| Frequency (MHz)                   |                 |
| Wireless Standard                 |                 |
| Color                             | White           |

| CODE | DESCRIPTION |
|------|-------------|
|------|-------------|

**XTS 5IP WH  
840CH-0090**

**Full-touch speaker video intercom for IP360 system, 5" TFT touch screen display, with Graphical User Interface - white.**

Wall monitor with 5" TFT touch screen display with Moth-Eye technology. User interface for management of the functions of video entry phone, intercom calls, video recording, text messages. It uses the SIP protocol and G711 audio codec and H.264 video codec. RJ45 port for network connection, PoE or local power supply. Integrated web service for configuration and firmware updates. A bracket is included for wall installation on 503 box (horizontal or vertical) and on round box Ø 60 mm. Suitable for built-in installation with dedicated box. Compatible with IP360 systems.

