







## SPEAKER VIDEO INTERCOM WITH 5" AND 7" TOUCH SCREEN DISPLAY



### COMPATIBLE SYSTEMS



-  **Recess mounted**  
11 mm thick
-  **Wall mounted**  
24 mm thick
-  **Video intercom version**
-  **7" display**
-  **5" display**
-  **Version for the hearing impaired**
-  **Speaker audio**

Do you want a design product with a load of technology? Choose XTS. This is the new range of video entry panel systems, available with 7" and 5" monitors - fully touch screen. The minimal design and quality of the materials exalt its elegance, whether you choose the white or black version. The high-resolution glass screen with Optical Bonding technology ensures perfect viewing in all lighting conditions. Having WiFi, both in the X1 and IP versions, makes it the choice for managing the video intercom system and opening the front door from a smartphone.

### PLUS

- Speaker audio
- Capacitive touch screen
- Display with Optical Bonding anti-glare technology
- Auxiliary/porter call functions
- Intercom calls
- "Panic" key for emergency calls to the porter
- Adjust/exclude ringtone (with alert LED when excluded)
- Self-inserting video from entry panels
- Video answering service and video recording
- Local or POE power supply

### AVAILABLE VERSIONS




Recess mounted



Wall mounted

### DIMENSIONS (MM)





**PLUS**

- Full-duplex speaker audio
- 7" TFT display Full touch-screen with Optical Bonding anti-glare technology for enhanced readability in brightly lit settings
- RJ45 port for directly connecting to the Ethernet
- On-board WiFi for remotely controlling calls
- Local or PoE (Powered over Ethernet) power supply
- Customizable user interface with UI Creator software
- Up to 19 mobile devices for managing the system from any remote location
- Configurable quick controls (default main entrance door-opener)
- List of AUX commands for activating auxiliary functions
- "Panic" function for emergency calls to the porter (if present on the system)
- Exclude ringtone key (the alert LED lights up when silenced)
- Self-inserting video of entry panels with cyclic selection
- Unlimited intercom calls to other receivers and mobile devices
- Contacts list and favorites list
- Video answering service, stores up to 100, 10-second audio and video messages.
- Audio and video recording during conversations
- Sending and receiving text messages from the porter
- Live feeds of the connected IP video cameras
- Automatic opening function during business hours
- Standard SIP protocol, H.264 video codec, G711 audio codec
- On-board web server for configuring and managing via the browser



**XTS 7IP WH WIFI**  
**840CH-0060**

**TECHNICAL CHARACTERISTICS**

MODELS	XTS 7IP WH WIFI
Dimensions (mm)	185 x 129 x 24
Local power supply (V)	14 ÷ 18 DC
PoE power supply	IEEE 802.3af-PD
Consumption in stand-by mode (mA)	340
Max. absorption (mA)	420
Operating temperature (°C)	0 ÷ +40
Protection rating (IP)	30
Video standard	H.264
Frequency (MHz)	2.412 - 2.472
Wireless Standard	IEEE 802.11b/g/n
Color	White

**CODE DESCRIPTION**

**XTS 7IP WH WIFI**  
**840CH-0060**

**Full touch speaker video intercom for IP360 system, 7" TFT touch-screen display, WiFi and Graphical User Interface - white.**

Wall monitor with 7" TFT touch-screen display with Optical Bonding technology, integrated Wi-Fi for remote calls on smartphones running the dedicated app. User interface for managing video intercom functions, intercom calls, video-messaging, and text messaging. It uses SIP protocol and G711 audio codec and H.264 video codec. RJ45 port for network, PoE or local connection. On-board web server for configuring and updating firmware. It includes brace for wall-mounting on 503 box (horizontal) and Ø 60 mm round box. Ready for flush mounting with dedicated box. Compatible with IP360 system.





### PLUS

- Full-duplex speaker audio
- 7" TFT display Full touch-screen with Optical Bonding anti-glare technology for enhanced readability in brightly lit settings
- RJ45 port for directly connecting to the Ethernet
- On-board WiFi for remotely controlling calls
- Local or PoE (Powered over Ethernet) power supply
- Customizable user interface with UI Creator software
- Up to 19 mobile devices for managing the system from any remote location
- Configurable quick controls (default main entrance door-opener)
- List of AUX commands for activating auxiliary functions
- "Panic" function for emergency calls to the porter (if present on the system)
- Exclude ringtone key (the alert LED lights up when silenced)
- Self-inserting video of entry panels with cyclic selection
- Unlimited intercom calls to other receivers and mobile devices
- Contacts list and favorites list
- Video answering service, stores up to 100, 10-second audio and video messages.
- Audio and video recording during conversations
- Sending and receiving text messages from the porter
- Live feeds of the connected IP video cameras
- Automatic opening function during business hours
- Standard SIP protocol, H.264 video codec, G711 audio codec
- On-board web server for configuring and managing via the browser

## XTS 7IP BK WIFI 840CH-0070

### TECHNICAL CHARACTERISTICS

MODELS	XTS 7IP BK WIFI
Dimensions (mm)	185 x 129 x 24
Local power supply (V)	14 ÷ 18 DC
PoE power supply	IEEE 802.3af-PD
Consumption in stand-by mode (mA)	340
Max. absorption (mA)	420
Operating temperature (°C)	0 ÷ +40
Protection rating (IP)	30
Video standard	H.264
Frequency (MHz)	2.412 - 2.472
Wireless Standard	IEEE 802.11b/g/n
Color	Black

CODE	DESCRIPTION
------	-------------

**XTS 7IP BK WIFI  
840CH-0070**

**Full-touch speaker video intercom for IP360 system, 7" TFT touch screen display, Wi-Fi and Graphical User Interface - black.**

Wall monitor with 7" TFT touch-screen display with Optical Bonding technology, integrated Wi-Fi for remote calls on smartphones running the dedicated app. User interface for managing video intercom functions, intercom calls, video-messaging, and text messaging. It uses SIP protocol and G711 audio codec and H.264 video codec. RJ45 port for network, PoE or local connection. On-board web server for configuring and updating firmware. It includes brace for wall-mounting on 503 box (horizontal) and Ø 60 mm round box. Ready for flush mounting with dedicated box. Compatible with IP360 system.





**PLUS**

- Full-duplex speaker audio
- 7" TFT display Full touch-screen with Optical Bonding anti-glare technology for enhanced readability in brightly lit settings
- RJ45 port for directly connecting to the Ethernet
- On-board WiFi for remotely controlling calls
- Local or PoE (Powered over Ethernet) power supply
- Customizable user interface with UI Creator software
- Up to 19 mobile devices for managing the system from any remote location
- Configurable quick controls (default main entrance door-opener)
- List of AUX commands for activating auxiliary functions
- "Panic" function for emergency calls to the porter (if present on the system)
- Exclude ringtone key (the alert LED lights up when silenced)
- Self-inserting video of entry panels with cyclic selection
- Unlimited intercom calls to other receivers and mobile devices
- Contacts list and favorites list
- Video answering service, stores up to 100, 10-second audio and video messages.
- Audio and video recording during conversations
- Sending and receiving text messages from the porter
- Live feeds of the connected IP video cameras
- Automatic opening function during business hours
- Standard SIP protocol, H.264 video codec, G711 audio codec
- On-board web server for configuring and managing via the browser
- Suitable for hearing aid users



**XTS 7IP WH WFBF**  
**840CH-0080**

**TECHNICAL CHARACTERISTICS**

MODELS	XTS 7IP WH WFBF
Dimensions (mm)	185 x 129 x 24
Local power supply (V)	14 ÷ 18 DC
PoE power supply	IEEE 802.3af-PD
Consumption in stand-by mode (mA)	340
Max. absorption (mA)	420
Operating temperature (°C)	0 ÷ +40
Protection rating (IP)	30
Video standard	H.264
Frequency (MHz)	2.412 - 2.472
Wireless Standard	IEEE 802.11b/g/n
Color	White

**CODE DESCRIPTION**

**XTS 7IP WH WFBF 840CH-0080** Full-touch speaker video intercom for IP360 system, 7" TFT touch screen display, Wi-Fi and Graphical User Interface - white.

Wall monitor with 7" TFT touch-screen display with Optical Bonding technology, integrated Wi-Fi for remote calls on smartphones running the dedicated app. User interface for managing video intercom functions, intercom calls, video-messaging, and text messaging. It uses SIP protocol and G711 audio codec and H.264 video codec. RJ45 port for network, PoE or local connection. On-board web server for configuring and updating firmware. It has an audio-frequency induction system for hearing aids, in the "T" position. It includes bracket for wall-mounting on horizontal 503-type boxes and Ø 60 mm round boxes. Ready for flush mounting with dedicated box. Compatible with IP360 system.





### PLUS

- Full-duplex speaker audio
- 5" TFT display Full touch-screen with Optical Bonding anti-glare technology for enhanced readability in brightly lit settings
- RJ45 port for directly connecting to the Ethernet
- Local or PoE (Powered over Ethernet) power supply
- Customizable user interface with UI Creator software
- Configurable quick controls (default main entrance door-opener)
- List of AUX commands for activating auxiliary functions
- "Panic" function for emergency calls to the porter (if present on the system)
- Audio video settings: ringtone volume, display brightness, interface backgrounds
- Different melodies for entry panels and landings
- Exclude ringtone key (the alert LED lights up when silenced)
- Self-inserting video of entry panels with cyclic selection
- Unlimited calls to other receivers and smartphones and tablets
- Contacts list and favorites list
- Video answering service, stores up to 100, 10-second audio and video messages.
- Audio and video recording during conversations
- Sending and receiving text messages from the porter
- Live feeds of the connected IP video cameras
- Business function: for automatic door opening during business hours
- Block display function for cleaning
- Standard SIP protocol, H.264 video codec, G711 audio codec
- On-board web server for configuring and managing via the browser

## XTS 5IP WH 840CH-0090

### TECHNICAL CHARACTERISTICS

MODELS	XTS 5IP WH
Dimensions (mm)	138 x 98 x 24
Local power supply (V)	14 ÷ 18 DC
PoE power supply	IEEE 802.3af-PD
Consumption in stand-by mode (mA)	270
Max. absorption (mA)	330
Operating temperature (°C)	0 ÷ +40
Protection rating (IP)	30
Video standard	H.264
Color	White

CODE	DESCRIPTION
------	-------------

**XTS 5IP WH  
840CH-0090**

**Full-touch speaker video intercom for IP360 system, 5" TFT touch screen display, with Graphical User Interface - white.**

Wall monitor with 5" TFT touch screen display with Optical Bonding technology. User interface for managing video intercom functions, intercom calls, video-messaging, and text messaging. It uses SIP protocol and G711 audio codec and H.264 video codec. RJ45 port for network, PoE or local connection. On-board web server for configuring and updating firmware. It includes brace for wall-mounting on 503 box (horizontal) and Ø 60 mm round box. Ready for flush mounting with dedicated box. Compatible with IP360 system.





**PLUS**

- Full-duplex speaker audio
- 5" TFT display Full touch-screen with Optical Bonding anti-glare technology for enhanced readability in brightly lit settings
- RJ45 port for directly connecting to the Ethernet
- Local or PoE (Powered over Ethernet) power supply
- Customizable user interface with UI Creator software
- Configurable quick controls (default main entrance door-opener)
- List of AUX commands for activating auxiliary functions
- "Panic" function for emergency calls to the porter (if present on the system)
- Audio video settings: ringtone volume, display brightness, interface backgrounds
- Different melodies for entry panels and landings
- Exclude ringtone key (the alert LED lights up when silenced)
- Self-inserting video of entry panels with cyclic selection
- Unlimited calls to other receivers and smartphones and tablets
- Contacts list and favorites list
- Video answering service, stores up to 100, 10-second audio and video messages.
- Audio and video recording during conversations
- Sending and receiving text messages from the porter
- Live feeds of the connected IP video cameras
- Business function: for automatic door opening during business hours
- Block display function for cleaning
- Standard SIP protocol, H.264 video codec, G711 audio codec
- On-board web server for configuring and managing via the browser

**XTS 5IP BK**  
**840CH-0100**

**TECHNICAL CHARACTERISTICS**

MODELS	XTS 5IP BK
Dimensions (mm)	138 x 98 x 24
Local power supply (V)	14 ÷ 18 DC
PoE power supply	IEEE 802.3af-PD
Consumption in stand-by mode (mA)	270
Max. absorption (mA)	330
Operating temperature (°C)	0 ÷ +40
Protection rating (IP)	30
Video standard	H.264
Color	Black

**CODE DESCRIPTION**

**XTS 5IP BK**  
**840CH-0100**

**Full-touch speaker video intercom for IP360 system, 5" TFT touch screen display, with Graphical User Interface - black.**

Wall monitor with 5" TFT touch screen display with Optical Bonding technology. User interface for managing video intercom functions, intercom calls, video-messaging, and text messaging. It uses SIP protocol and G711 audio codec and H.264 video codec. RJ45 port for network, PoE or local connection. On-board web server for configuring and updating firmware. It includes brace for wall-mounting on 503 box (horizontal) and Ø 60 mm round box. Ready for flush mounting with dedicated box. Compatible with IP360 system.





### PLUS

- Half-duplex speaker audio
- 7" TFT display Full touch-screen with Optical Bonding anti-glare technology for enhanced readability in brightly lit settings
- On-board WiFi for remotely controlling calls over smartphones and tablets running the specific App
- Local power supply 14 -18 VDC
- Up to 4 mobile device for managing the system from any remote location
- Configurable quick controls: main entrance door-opener, auxiliary command
- List of AUX commands for activating auxiliary functions
- "Panic" function for emergency calls to the porter (if present on the system)
- Audio video settings: ringtone volume, display brightness, interface backgrounds
- Different melodies for entry panels and landings
- Exclude ringtone key (the alert LED lights up when silenced)
- Self-inserting video of entry panels with cyclic selection
- Intercom calls to other receivers and smartphones and tablets
- Contacts list and favorites list
- Video answering service, stores up to 100, 10-second audio and video messages.
- Audio and video recording during conversations
- Live feeds of the connected IP video cameras
- Business function: for automatic door opening during business hours
- Block display function for cleaning
- Standard SIP protocol, H.264 video codec, G711 audio codec
- On-board web server for configuring and managing via the browser

## XTS 7 WH WIFI 840CH-0030

### TECHNICAL CHARACTERISTICS

MODELS	XTS 7 WH WIFI
Dimensions (mm)	185 x 129 x 24
Local power supply (V)	14 ÷ 18 DC
Local absorption (mA)	520
Consumption in stand-by mode (mA)	360
Operating temperature (°C)	0 ÷ +40
Protection rating (IP)	30
Video standard	PAL/NTSC
Frequency (MHz)	2.412 - 2.472
Wireless Standard	IEEE 802.11b/g/n
Color	White

#### CODE

#### DESCRIPTION

**XTS 7 WH WIFI  
840CH-0030**

**Full-touch speaker video intercom for X1 system, 7" TFT touch screen display, Wi-Fi and Graphical User Interface - white.**

Wall monitor with 7" TFT touch-screen display with Optical Bonding technology, integrated Wi-Fi for remote calls on smartphones running the dedicated app. User interface for managing video intercom functions, intercom calls, video-messaging. It uses SIP protocol and G711 audio codec and H.264 video codec. Local power supply 14-18 VDC. On-board web server for configuring and updating firmware. It includes brace for wall-mounting on 503 box (horizontal) and Ø 60 mm round box. Ready for recess-mounting with corresponding box. Compatible with the X1 and XIP systems.





**PLUS**

- Half-duplex speaker audio
- 7" TFT display Full touch-screen with Optical Bonding anti-glare technology for enhanced readability in brightly lit settings
- On-board WiFi for remotely controlling calls
- Local power supply 14 -18 V DC
- Up to 4 connectable mobile devices per unit
- Configurable quick controls (default main entrance door-opener)
- List of AUX commands for activating auxiliary functions
- "Panic" function for emergency calls to the porter (if present on the system)
- Exclude ringtone key (the alert LED lights up when silenced)
- Self-inserting video of entry panels with cyclic selection
- Unlimited intercom calls to other receivers and mobile devices
- Contacts list and favorites list
- Video answering service, stores up to 100, 10-second audio and video messages.
- Audio and video recording during conversations
- Live feeds of the connected IP video cameras
- Automatic opening function during business hours
- Standard SIP protocol, H.264 video codec, G711 audio codec
- On-board web server for configuring and managing via the browser



**XTS 7 BK WIFI**  
**840CH-0040**

**TECHNICAL CHARACTERISTICS**

MODELS	XTS 7 BK WIFI
Dimensions (mm)	185 x 129 x 24
Local power supply (V)	14 ÷ 18 DC
Local absorption (mA)	520
Consumption in stand-by mode (mA)	360
Operating temperature (°C)	0 ÷ +40
Protection rating (IP)	30
Video standard	PAL/NTSC
Frequency (MHz)	2.412 - 2.472
Wireless Standard	IEEE 802.11b/g/n
Color	Black

**CODE DESCRIPTION**

**XTS 7 BK WIFI**  
**840CH-0040**

**Full-touch speaker video intercom for X1 system, 7" TFT touch screen display, Wi-Fi and Graphical User Interface - black.**

Wall monitor with 7" TFT touch-screen display with Optical Bonding technology, integrated Wi-Fi for remote calls on smartphones running the dedicated app. User interface for managing video intercom functions, intercom calls, video-messaging. It uses SIP protocol and G711 audio codec and H.264 video codec. Local power supply 14-18 VDC. On-board web server for configuring and updating firmware. It includes brace for wall-mounting on 503 box (horizontal) and Ø 60 mm round box. Ready for recess-mounting with corresponding box. Compatible with the X1 and XIP systems.







## PLUS

- Suitable for hearing aid users
- Half-duplex speaker audio
- 7" TFT display Full touch-screen with Optical Bonding anti-glare technology for enhanced readability in brightly lit settings
- On-board WiFi for remotely controlling calls over smartphones and tablets running the specific App
- Local power supply 14 -18 VDC
- Up to 4 mobile device for managing the system from any remote location
- Configurable quick controls: main entrance door-opener, auxiliary command
- List of AUX commands for activating auxiliary functions
- "Panic" function for emergency calls to the porter (if present on the system)
- Audio video settings: ringtone volume, display brightness, interface backgrounds
- Different melodies for entry panels and landings
- Exclude ringtone key (the alert LED lights up when silenced)
- Self-inserting video of entry panels with cyclic selection
- Intercom calls to other receivers and smartphones and tablets
- Contacts list and favorites list
- Video answering service, stores up to 100, 10-second audio and video messages.
- Audio and video recording during conversations
- Live feeds of the connected IP video cameras
- Business function: for automatic door opening during business hours
- Block display function for cleaning
- Standard SIP protocol, H.264 video codec, G711 audio codec
- On-board web server for configuring and managing via the browser

## XTS 7 WH WFBF 840CH-0050

### TECHNICAL CHARACTERISTICS

MODELS	XTS 7 WH WFBF
Dimensions (mm)	185 x 129 x 24
Local power supply (V)	14 ÷ 18 DC
Local absorption (mA)	520
Consumption in stand-by mode (mA)	360
Operating temperature (°C)	0 ÷ +40
Protection rating (IP)	30
Video standard	PAL/NTSC
Frequency (MHz)	2.412 - 2.472
Wireless Standard	IEEE 802.11b/g/n
Color	White

### CODE DESCRIPTION






**XTS 7 WH WFBF  
840CH-0050**

**Full-touch speaker video intercom for X1 system, 7" TFT touch screen display, Wi-Fi and Graphical User Interface, on-board teleloop - white.**

Wall monitor with 7" TFT touch-screen display with Optical Bonding technology, integrated Wi-Fi for remote calls on smartphones running the dedicated app. User interface for managing video intercom functions, intercom calls, video-messaging. It uses SIP protocol and G711 audio codec and H.264 video codec. Local power supply 14-18 VDC. On-board web server for configuring and updating firmware. It has an audio-frequency induction system for hearing aids, in the "T" position. Includes bracket for wall mounting on horizontal 503-type boxes and Ø 60 mm round boxes. Ready for flush mounting with dedicated box. Compatible with the X1 and XIP systems.



**Accessories**

CODE	DESCRIPTION	
<b>XTS 7SI</b> <b>840XC-0080</b>	<b>Recess-mounting box for XTS 7 entry panels.</b> Plastic recess-mounting box with pre-punched holes for passing the cables, complete with mortar guard.	
<b>XTS 5SI</b> <b>840XC-0090</b>	<b>Recess-mounting box for XTS 5 entry panels.</b> Plastic recess-mounting box with pre-punched holes for passing the cables, complete with mortar guard.	
<b>XTS 7SIC</b> <b>840XC-0100</b>	<b>Recess-mounting box for plasterboard walls for XTS 7 entry panels.</b> Plastic recess-mounting box with pre-punched holes for passing cables, ideal for plasterboard walls of up to 22 mm in thickness.	
<b>XTS 5SIC</b> <b>840XC-0110</b>	<b>Recess-mounting box for plasterboard walls for XTS 5 entry panels.</b> Plastic recess-mounting box with pre-punched holes for passing cables, ideal for plasterboard walls of up to 22 mm in thickness.	
<b>XTS 7KT</b> <b>840XC-0120</b>	<b>Desktop stand for XTS 7 entry panels.</b> Plexiglass 10 mm-thick stand, supplied with white 3 m CAT5 cable and terminal board cover with PMMA laminate - metallic gray.	
<b>XTS 5KT</b> <b>840XC-0130</b>	<b>Desktop stand for XTS 5 entry panels.</b> Plexiglass 10 mm-thick stand, supplied with white 3 m CAT5 cable and terminal board cover with PMMA laminate - metallic gray.	